APS260C Cart System Spec Sheet

Caregility

System Specifications

Call Resolution	up to 720P/30
Supported Protocols	WebRTC
Video Codecs	VP8
Audio Output	14W Mono Channel
Speaker	2 x 1.50" Speaker
Microphone	7 Microphone Array
Audio codecs	Opus
Security	AES (128-bit), DTLS, SSL
Bandwidth	1.2Mpbs
Operating System	Hardened Linux
CPU	Intel i5-6200U 6th generation 2.3 GHz Dual Core (Fanless)
RAM	8GB
HDD	SSD MLC 128GB
All In One Display	22" 24/7 Medical Cart Computer
Camera	Inverted 1080P Motorized PTZ 20x Optical 2x Digital Zoom (40x Combined)
Camera Horizontal Viewing Angle	60 Degrees
IR Light	(1) 21 Inch LED Bar – 850nm

Network and Power Requirements

Wired Network	10/100/1000 Ethernet, Wired	
Wireless Network	WIFI 5 802.11 ac - BT 5.1 2.4/5 GHz Bands	
Cart Power Input	110/220 VAC Auto switching	
Cart Power Consumption	65W	
Battery Packs	Two 10.95V li-on batteries. Hot swappable battery Packs, 60W, 11.4V, 8550 mAh	
Est. Battery Run Time	5.5 Hours In Call (Fully Charged)	
Est. Battery Charge Time	3-4 Hours (Actual based on battery age and condition)	
Cart AC Adapter In	24 VDC	

System Dimensions

Cart Dimensions (WxDxH) Inches/(mm)	23.4x28.9x72.4 (594x734x1839)
Cart Weight	71 Lbs. (32.2KG)
Shipping Weight	110 lbs. (50 kg)